



SIZE	ØD±0.2	L±1.0	E±2.0	H±1.0	A±1.0	B±1.0	C±1.0	F±1.0	N±0.05	W1±0.5	W2±0.5	M	O
1/4"	11.2	55	110	60	7.0	16.0	23.5	38.5	5.0	12.7	28.5	5/16"-24UNF	3/16"-24UNC
3/8"	12.5	55	110	60	7.0	16.0	23.5	38.5	5.0	12.7	28.5	5/16"-24UNF	3/16"-24UNC
1/2"	15.0	65	110	65	8.0	18.1	26.0	45.0	5.0	12.7	28.5	5/16"-24UNF	3/16"-24UNC
3/4"	19.0	74	136	70	8.0	18.3	26.7	48.0	6.4	22.4	35.0	3/8"-24UNF	3/16"-24UNC
1"	25.0	88	165	80	10.2	23.0	32.5	58.5	8.0	25.4	38.1	7/16"-20UNF	3/16"-24UNC
1-1/4"	32.0	101	165	86	10.2	23.5	32.0	64.3	8.0	25.4	38.1	7/16"-20UNF	3/16"-24UNC
1-1/2"	38.0	109	200	100	14.1	29.0	40.1	77.0	9.5	25.4	49.2	9/16"-18UNF	1/4"-20UNC
2"	49.0	126	200	106	14.3	30.0	36.7	85.0	9.5	25.4	49.2	9/16"-18UNF	1/4"-20UNC

Two-Piece Fire-Safe Full Port 2000 PSI Ball Valve

REVISION 00

SCALE Free

UNIT mm

INSPECTED BY

DRAWN BY

SIZE 1/4"~2"

MAT'L ASTM A351 Gr.CF8M

DATE Sep. 13, 2010

MODEL 2-2F

TYPE D

FILE AD22F-663xx-PGF